

B2200H SERIES DATA SHEET



SHOCK TUBE TESTED • THIRD PARTY EVALUATION • MANUFACTURED IN THE USA

WINDOW TYPE	FRAME DEPTH (inches)	SERIES	DESIGNED BLAST PRESSURE (psi)	POSITIVE PHASE IMPULSE (psi-msec)	WINDOW SIZE (inches)	GLAZING COMPOSITION (inches)	TESTING & CERTIFICATIONS		
							Test Methods	Qualified	Certification
Historic Double Hung	4	B2200H	6.6	45	49¾ x 67¾	¼ annealed, ½ as, ¼ lami	ASTM F 1642	ASTM "Minimal Hazard" GSA Condition 2 UFC 4-010-01	Independent Test Report

Products comply with Unified Facilities Criteria UFC 4-010-01; DoD Minimum Antiterrorism Standards for Buildings

STANDARD FEATURES

- Double Hung Side-Load windows for blast mitigation
- Provides GSA level C protection against explosive attacks
- Meets DoD UFC 4-010-01 criteria
- Utilizes standard locking hardware
- Trim & clip or receptor anchoring system
- 1" insulating glass construction using industry standard laminated technology
- Mulls to 4" frame fixed and operable products
- Sash easily removes from frame for maintenance & cleaning
- Removable take-out clips to prevent unauthorized sash removal
- Full-length extruded lift handles
- Exterior beveled glazing leg (putty-glazed look)



Series B2200H Meets GSA Condition 2

Window series: B2200H Double Hung (Side-Load) — General Specifications & Details

- Nominal Frame/Sill Wall Thickness: 0.062/0.094"
- Mulls to operable and fixed units with 4" frame depth
- Test Size:
50" x 68"
- Glazing:
¼" annealed, ½" spacer, ¼" laminated
- Muntins: Grids between lites of IG unit or exterior-applied
- Curved Shapes: Radius tops and arches available with mull fixed units
- Maximum Sash Weight: Standard balancing of both sash to 80 lbs
Optional heavy-duty system to 120 lbs. Depends on height-to-width ratio (please contact factory)

- Finish Options:
AAMA 2603 — Standard acrylic or polyester
AAMA 2604 — 2 coat 50% fluoropolymer
AAMA 2605 — 2 coat fluoropolymer 70% kynar
Powder Coat
Anodized
- Hardware:
White bronze sweep lock with keeper
- Accessories:
Fixed Lite Option System: 1400
Frame Family: 4"
Mullions: Stacking: Integral & fixed-stack mull
Side: 3-piece mull
Panning: Available
Trims: Available
Receptor Systems: Available
- Exceptions: Call Graham sales rep or see website for more information

Our products are tested to the standards of and certified by the American Architectural Manufacturer's Association and the National Fenestration Rating Council.

