

0200 SERIES DATA SHEET

TYPE	AAMA RATING & TEST SIZE	AIR (cfm/ft ²) at 50 mph	WATER (psf)	DESIGN PRESSURE (psf)	STRUCTURAL OVERLOAD (psf)	U-VALUE (BTU/hr/ ft ² /°F) ¹	CRF	STC	OITC
HORIZONTAL SLIDING	AW-PG65 99 x 79	0.19	12.11	65.16	97.74	0.51 – 0.60	58	29 - 36	23 - 31
	HS-HC40 99 x 79	0.28	9.20	40.13	60.19	0.51 – 0.60	58	29 - 36	23 - 31

NOTE: The air infiltration and water resistance performance values provided above were achieved in a controlled lab environment. Performance of our products in the field will vary depending on product configurations, installation methods, and ambient conditions. AAMA 502 "Voluntary Specification for Field Testing of Newly Installed Fenestration Products" should be adhered to for testing installed products. | ¹ U-values will vary depending upon glazing selected.

0200 SERIES QUICK VIEW:

A horizontal sliding commercial window that mulls to 4" frame fixed and operable products. Stainless steel ball bearing rollers adjust to two positions. All sash, fixed and operating, are removable from inside. White bronze hardware



STANDARD FEATURES

- Mulls to 4" frame fixed and operable products
- All sash, fixed and operating, are removable from inside
- Stainless steel ball bearing rollers adjust to two positions
- Full-length integral pull rails
- White bronze hardware

OPTIONAL FEATURES

- Anti-takeout blocks to restrict sash removal
- Three panel can operate as XOX, OXO, XXX
- Extruded latch at jamb
- Flange frame 2"
- Bypassing sash (not available with extruded locks) for easy cleaning without removing

Window series: 0200 Horizontal Sliding — General Specifications & Details

- Nominal Frame/Sill Wall Thickness: 0.062/0.078"
- Applications: Industrial, Educational, Hospitals, and Acoustical
- Max. Test size: 8'3" x 6'7"
- Mulling: Mulls to operable and fixed units with 4" frame depth
- Glazing Thickness:
 - Single lite to 1/4"; Insulating to 1"; bead glazed
- Muntins: Grids between lites of IG or dual-glaze unit; or exterior applied in conjunction with 3/16" IG unit
- Curved Shapes: Radius tops and arches available with mull fixed units (Series 1400)

- Finish Options:
 - AAMA 2603 — Standard acrylic or polyester
 - AAMA 2604 — 2 coat 50% fluoropolymer
 - AAMA 2605 — 2 coat fluoropolymer 70% kynar
 - Powder Coat
 - Anodized
- Hardware:
 - 2 position stainless steel roller ball bearings
 - White bronze hardware
- Accessories:
 - Frame Family: 4"
 - Fixed Lite Option System: 1400
 - Mullions:
 - Stacking: Integral & fixed-stack mull
 - Side: 3-piece-mull
 - Panning: Available
 - Trims: Available
 - Receptor Systems: Available
- Exceptions: Call Graham sales rep or see website for more information

Our products are tested to the standards of and certified by the American Architectural Manufacturer's Association and the National Fenestration Rating Council.

