

7500 SERIES DATA SHEET



TYPE	AAMA RATING & TEST SIZE	AIR (cfm/ft ²) at 50 mph	WATER (psf)	DESIGN PRESSURE (psf)	STRUCTURAL OVER-LOAD (psf)	U-VALUE (BTU/hr/ft ² /°F) ¹	CRF
DUAL ACTION	DAW-HC65 48 x 72	0.15	10	65	98	0.44 – 0.59	53
	DAW-HC40 60 x 99			40	60	0.44 – 0.59	53

¹U-values will vary depending upon glazing selected

7500 SERIES QUICK VIEW:

Dual-action, tilt-and-turn aluminum frame mulls horizontally or vertically to 2 1/4" frame fixed and operable windows. Vent has flush design for aesthetic appeal.

STANDARD FEATURES

- Sloped-exterior glazing leg simulates putty-glazed profile
- Mulls horizontally or vertically to 2 1/4" frame fixed and operable products
- Multi-point locking hardware
- Applied grids available

OPTIONAL FEATURES

- Hardware can be painted similar to selected door frame color
- Blast-resistant (B7500) version available



Window series: 7500 Dual Action — General Specifications & Details

- Nominal Frame/Sill Wall Thickness: 0.080"
- Applications: Industrial, Educational and Hospitals
- Max. Test size: Fixed 5'0" x 8'3"
- Glazing Options:
 - Insulating: 1" IG available with options
- Muntins: Between-the-glass or exterior applied

- Finish Options:
 - AAMA 2603 — Standard acrylic or polyester
 - AAMA 2604 — 2 coat 50% fluoropolymer
 - AAMA 2605 — 2 coat fluoropolymer 70% kynar
 - Powder Coat
 - Anodized
- Hardware (Operable Units):
 - Multi-point/dual locking hardware
- Accessories:
 - Frame Family: 2 1/4"
 - Fixed Lite Option System: 6500 and 6600
 - Mullions:
 - Stacking: Integral & fixed-stack mull
 - Side: 3-piece-mull
 - Panning: Available
 - Trims: Available
 - Receptor Systems: Available
- Exceptions: Call Graham sales rep or see website for more information.

Our products are tested to the standards of and certified by the American Architectural Manufacturer's Association and the National Fenestration Rating Council.



Dual Action - 2 1/4"



Series: 7500

Manufacturing Code: 7501

Drawing 1/2 Scale - For Custom Size Drawing Contact Graham

Note: Sealant Not Shown On Details. Consult Technical Services At Factory For Sealing Procedures.

