

GT6200 SL SINGLE-LEVER OPERATOR

TYPE	AAMA RATING & TEST SIZE	AIR (cfm/ft ²) at 50 mph	WATER (psf)	DESIGN PRESSURE (psf)	STRUCTURAL OVERLOAD (psf)	U-VALUE (BTU/hr/ft ² /°F) ¹	STC	OITC
OUT-SWING CASEMENT	AW-PG75 42 x 72	0.06	15	75	112.5	0.29 – 0.38	34 - 40	27 - 32

NOTE: The air infiltration and water resistance performance values provided above were achieved in a controlled lab environment. Performance of our products in the field will vary depending on product configurations, installation methods, and ambient conditions. AAMA 502 "Voluntary Specification for Field Testing of Newly Installed Fenestration Products" should be adhered to for testing installed products. | ¹ U-values will vary depending upon glazing selected.

GT6200 SL SERIES QUICK VIEW:

Out-swing casement window with single point, multi-functioning handle. Unlock, lock, open, close, stay bar, and limit device all in one with minimal force required for operation.

STANDARD FEATURES

- Multi-point locks
- Single-point - lever operation
- Full screen, no wickets required
- 2¾" or 3⅜" frame depth
- Concealed hinges (barrel hinges optional)
- Limit arm with custodial override
- Thermal strut technology for superior U-values
- Euro-groove design for hardware versatility
- EPDM dry glazed to accommodate field installation

OPTIONAL FEATURES

- ADA operational forces
- Multi-sided lock locations
- Operating lever does not need centered on jamb (can be located as close as 12" from sill)
- Exterior applied muntin grids
- Dual finish (two-tone color) option
- Configured to meet NYC Falls Prevention



Window series: GT6200 SL Single-Lever Operator — General Specifications & Details

- Applications: Industrial, Educational, Hospitals and Acoustical
- Max Test Size: 3.5' x 6'
- Glazing Options:
 - Insulating: 1" and 1⅝" IG available;
- Muntins: Between-the-glass grids, true-divided lites, and applied grids available
- Finish Options:
 - AAMA 2603 — Standard acrylic or polyester
 - AAMA 2604 — 2 coat 50% fluoropolymer
 - AAMA 2605 — 2 coat fluoropolymer 70% kynar
 - Powder Coat
 - Anodized

- Hardware (Operable Units):
 - Hinges: Concealed Euro; unlock, lock, open, close, stay bar and limit device all in one
- Accessories:
 - Frame Family: 2¾" or 3-3/8"
 - Fixed Lite Option System: GT6200
 - Mullions:
 - Stacking: Stack mull
 - Side: 3-piece-mull
 - Panning: Available
 - Trims: Available
 - Receptor Systems: Available
 - Screen: Security/vandal screen available
- Exceptions: Call Graham sales rep or see website for more information

Our products are tested to the standards of and certified by the American Architectural Manufacturer's Association and the National Fenestration Rating Council.

