

GT6 WINDOW SYSTEM

PRODUCT PERFORMANCE GUIDE

Window Series	GS6600			GT6700			GT6800		
	Casement	Projected	Fixed	Casement	Projected	Fixed	Casement	Projected	Fixed
AAMA Rating	AW-PG100	AW-PG100	AW-PG100	AW-PG100	AW-PG100	AW-PG100	AW-PG100	AW-PG100	AW-PG100
Test Size	36 x 60	60 x 36	60 x 99	36 x 60	60 x 36	60 x 99	36 x 60	60 x 36	60 x 99
Air Infiltration	<0.10	<0.10	<0.10	<0.10	<0.10	<0.10	<0.10	<0.10	<0.10
Water Resistance	12	12	12	12	12	12	12	12	12
Design Pressure	100	100	100	100	100	100	100	100	100
Uniform Load	150	150	150	150	150	150	150	150	150
CRF	56	56 ²	55	65	65 ²	66	70	74	73
U-Factor¹	0.46	0.47	0.35	0.41	0.42	0.35	0.38	0.39	0.30
SHGC	0.29	0.29	0.32	0.28	0.28	0.32	0.28	0.28	0.36
VT	0.47	0.47	0.55	0.47	0.47	0.55	0.47	0.47	0.61
CR	40	40	47	51	50	47	54	53	56

¹ U-Factor, SHGC, VT, and CR based on 1" IG with 1/4" Panes, Stainless Steel Spacer, 95% Argon Fill, Cardinal E272 Low-E Coat on Surface #2 | ² Estimated values



Casement

Projected

Fixed

