

## GX6800 SERIES DATA SHEET

TYPE	AAMA RATING & TEST SIZE	AIR (cfm/ft <sup>2</sup> ) at 50 mph	WATER (psf)	DESIGN PRESSURE (psf)	STRUCTURAL OVERLOAD (psf)	U-VALUE (BTU/hr/ft <sup>2</sup> /°F) <sup>1</sup>	CRF
PO CASEMENT	AW-PG100 36 x 60	0.01	15	100	150	0.28 - 0.38	76
PO AWNING	AW-PG100 60 x 36	0.03	15	100	150	0.27 - 0.38	-

NOTE: Performance of our products in the field will vary depending on product configurations, installation methods, and ambient conditions. AAMA 502 "Voluntary Specification for Field Testing of Newly Installed Fenestration Products" should be adhered to for testing installed products. <sup>1</sup> Values will vary depending upon glazing selected and sample size

### GX800 SERIES QUICK VIEW:

An energy efficient AW rated commercial window with a historic (beveled) profile. The GX6800 incorporates dual-strut technology and a center gasket for optimal air, water and thermal performance.

### STANDARD FEATURES

- 3-9/16" Frame Depth
- Superior joinery allows for larger units and more configurations
- Deep sloped exterior glazing leg
- Multiple glazing depths available
- Fixed/Operable intermediate design offers minimal sightlines
- Design allows multiple units into one opening simplifying installation
- Larger thermal strut technology for excellent thermal performance
- Dual finish (two-tone color) capability
- Concealed hinges
- Limited opening capability

### OPTIONAL FEATURES

- True and exterior applied muntin grids
- Equal sightline frame
- Single lever operator
  - Eliminates need for wicket screens
  - Can assist with meeting ADA operational forces
- Multi-point locking system



## Window series: GX6800 Casement/Projected — General Specifications & Details

- Applications: Industrial, Educational, Hospitals and Historic
- Max. Structural Test Size:
  - Casement: 3'0" x 5'0"
  - Projected: 5'0" x 3'0"
- Glazing Options:
  - Insulating: Multiple glazing depths available
- Muntins:
  - Between-the-glass grids, true-divided lites, and applied grids available
- Finish Options:
  - AAMA 2603 — Standard acrylic or polyester
  - AAMA 2604 — 2 coat 50% fluoropolymer
  - AAMA 2605 — 2 coat fluoropolymer 70% kynar
  - Powder Coat
  - Anodized

- Hardware Options (Operable Units):
  - Hinges: 4-bar stainless steel or stainless steel concealed hinges (casement only)
- Accessories:
  - Frame Family: 3-9/16"
  - Mullions:
    - Stacking: Integral & fixed-stack mull
    - Side: 3-piece-mull
    - Panning: Available
    - Trims: Available
    - Receptor Systems: Available
- Exceptions: Call Graham sales rep or see website for more information

Our products are tested to the standards of and certified by the American Architectural Manufacturer's Association and the National Fenestration Rating Council.

