

## HI2200 SERIES DATA SHEET

Type	Frame Depth (inches)	Missile		Design Pressure (psf)		Water (psf)	Test Size* (inches)
		Large	Small	Pos (+)	Neg (-)		
Double Hung Side-Load	4	✓		45	65	9.75	48 x 102 *

NOTE: The air infiltration and water resistance performance values provided above were achieved in a controlled lab environment. Performance of our products in the field will vary depending on product configurations, installation methods, and ambient conditions. AAMA 502 "Voluntary Specification for Field Testing of Newly Installed Fenestration Products" should be adhered to for testing installed products. | \* Contact Graham for available glazing and test configurations. | **Florida approval # 10083.2**

### STANDARD FEATURES

- Double hung window for hurricane-impact resistance
- Offers passive protection from wind-borne debris without shutters
- Block & tackle balances for superior operation
- Mulls to 4" frame fixed and operable products
- Sash easily removes from frame for maintenance & cleaning
- Removable take-out clips to prevent unauthorized sash removal
- Full-length extruded lift handles
- Exterior-beveled (putty) glazing leg on historic models

### OPTIONAL FEATURES

- Applied-profile muntin grids
- Dual-glazed split sash to permit high-performance glazing combinations
- Dual window available in some configurations
- Extruded automatic sill latches
- High-performance balances up to 120 lbs. per sash (larger sightlines at jambs)
- True colonial muntins
- White bronze hardware
- Self-balancing Class 5 balances
- Triple hung
- Simulated (fixed) double hung for historic applications
- Blast-resistant (B2200) versions available
- Dual finish (two-tone color) option (S2200)



## Window Series: HI2200 Double Hung — General Specifications & Details

• Tested To:

ASTM E1886, ASTM E1996, and/or TAS 201, TAS 202, TAS 203

• Max. Test Size:

4' x 8'5"

• Materials:

All frame sections shall be thermally broken extruded aluminum shapes produced from commercial quality 6063-T6 alloy

• Finish Options:

AAMA 2603, 2604, & 2605, as well as powder coat and anodize finishes, are all available in a wide range of colors

• Accessories:

Wide range of panning & trim options available

• Installation Methods:

Receptor & Subsill; Trim & Clip; Panning; 3-Piece Mullion

• Exceptions: Call Graham sales rep or see website for more information

Our products are tested to the standards of and certified by the American Architectural Manufacturer's Association and the National Fenestration Rating Council.

