

## HI6500 SERIES DATA SHEET

Type	Frame Depth (inches)	Missile		Design Pressure (psf)		Water (psf)	Test Size* (inches)
		Large	Small	Pos (+)	Neg (-)		
Fixed over Hopper	2 1/4	✓		50	50	12	45 1/4 x 33 1/8

NOTE: The air infiltration and water resistance performance values provided above were achieved in a controlled lab environment. Performance of our products in the field will vary depending on product configurations, installation methods, and ambient conditions. AAMA 502 "Voluntary Specification for Field Testing of Newly Installed Fenestration Products" should be adhered to for testing installed products. | \* Contact Graham for available glazing and test configurations

### STANDARD FEATURES

- Fixed window for hurricane-impact resistance
- Integral and fixed-stack mull for minimal sightlines
- Mulls horizontally or vertically to 2 1/4" frame fixed and operable products
- Receptor and panning systems available for installation
- Flush design of vent and frame for aesthetic appeal
- Frame and Vent 0.125" wall thickness

### OPTIONAL FEATURES

- Dual-glazed design offers optional:
  - High performance glazing combinations
  - Integral mini-blinds
  - Impact-resistant polycarbonate lite
- Stainless steel projected or aluminum hardware
- Hardware options to limit access to custodial use
- In-swing or out-swing on operable units
- Blast-resistant (B6500) version available



## Window Series: HI6500 Fixed — General Specifications & Details

#### • Tested To:

ASTM E1886, ASTM E1996, and/or TAS 201, TAS 202, TAS 203

#### • Max. Test Size:

3'7" x 2'7"

#### • Materials:

All frame sections shall be thermally broken extruded aluminum shapes produced from commercial quality 6063-T6 alloy

#### • Finish Options:

AAMA 2603, 2604, & 2605, as well as powder coat and anodize finishes, are all available in a wide range of colors

#### • Accessories:

Wide range of panning & trim options available

#### • Exceptions: Call Graham sales rep or see website for more information

Our products are tested to the standards of and certified by the American Architectural Manufacturer's Association and the National Fenestration Rating Council.

